

⚠️ WARNING ⚠️

1. **ALWAYS** connect gas cylinder to PRIMARY REDUCING VALVE.
2. **NEVER** try to connect cylinder directly to beverage container.
3. **ALWAYS** ensure upright cylinders are secure.
4. **ALWAYS** keep cylinder away from heat.
5. **NEVER** drop or throw cylinders.
6. **NEVER** try to unscrew fittings from beverage containers.
7. **ALWAYS** ventilate cellar after CO₂, nitrogen or mixed gas leakages.

CO₂, NITROGEN OR MIXED GAS CAN BE DANGEROUS

Please see BOC safety data sheets for further information.

Instructions for disconnecting gas cylinders

1. Close hand wheel on cylinder valve.
2. Unscrew high pressure hose or regulator nut.

Instructions for connecting gas cylinders

1. Check you have the correct gas cylinder - Suregas, Pumpgas or Suremix 30, 50, 60.
2. Always secure cylinder in upright position whilst in use.

3. Remove the dust cap.
4. Enter the high pressure hose or regulator connection into cylinder valve and tighten cylinder nut.
5. Do not overtighten nut.
6. Open hand wheel on cylinder valve.
7. In the event of a leak turn off the cylinder valve, remove any grit or dust particles on the washer and remake the connection.

**Your nearest
BOC Sureserve
service centre:**

08457 302 302

**Your BOC Sureserve
customer number:**

Your next delivery:

BOC
Sureserve 
Expertise you can trust

www.bocsureserve.co.uk