

Safety Data Sheet

Product :

Propane

Page :1/5

MSDS Nr : 302-00-0045BOC(A)

Version : 1.03

Date : 09/09/2003

Replaces version dated : 02/08/1994

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

Product name	Propane
Chemical formula	C3H8
Company identification	see heading and/or footer
Emergency phone numbers	see heading and/or footer

2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation	Substance.
Components/Impurities	Contains no other components or impurities which will influence the classification of the product.
CAS Nr	74-98-6
EC Nr (from EINECS)	200-827-9

3 HAZARDS IDENTIFICATION

Hazards identification	Liquefied gas Extremely flammable
------------------------	--------------------------------------

4 FIRST AID MEASURES

Inhalation	In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Skin/eye contact	In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Immediately flush eyes thoroughly with water for at least 15 minutes. Obtain medical assistance
Ingestion	Ingestion is not considered a potential route of exposure.

5 FIRE FIGHTING MEASURES

Specific hazards	Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	Incomplete combustion may form carbon monoxide.
Suitable extinguishing media	All known extinguishants can be used.
Specific methods	If possible, stop flow of product. Move away from the container and cool with water from a protected position.

Safety Data Sheet

Product :

Propane

Page :2/5

MSDS Nr : 302-00-0045BOC(A)

Version : 1.03

Date : 09/09/2003

Replaces version dated : 02/08/1994

Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.

Special protective equipment for fire fighters

Use self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions

Evacuate area.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Ensure adequate air ventilation.

Eliminate ignition sources.

Environmental precautions

Try to stop release.

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

Clean up methods

Ventilate area.

7 HANDLING AND STORAGE

Handling and storage

Ensure equipment is adequately earthed.

Suck back of water into the container must be prevented.

Purge air from system before introducing gas.

Do not allow backfeed into the container.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Keep away from ignition sources (including static discharges).

Segregate from oxidant gases and other oxidants in store.

Refer to supplier's container handling instructions.

Keep container below 50°C in a well ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal protection

Ensure adequate ventilation.

Do not smoke while handling product.

9 PHYSICAL AND CHEMICAL PROPERTIES

Molecular weight

44

Melting point

-188 °C

Boiling point

-42.1 °C

Safety Data Sheet

Product :**Propane**

Page :3/5

MSDS Nr : 302-00-0045BOC(A)

Version : 1.03

Date : 09/09/2003

Replaces version dated : 02/08/1994

Critical temperature	97 °C
Relative density, gas	1.5 (air=1)
Relative density, liquid	0.51 (water=1)
Vapour Pressure 20°C	8.3 bar
Solubility mg/l water	75 mg/l
Appearance/Colour	Colourless gas
Odour	Sweetish Poor warning properties at low concentrations. Stenchant often added
Flammability range	2.1 - 9.5 vol% in air.
Autoignition temperature	450 °C
Other data	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

10 STABILITY AND REACTIVITY

Stability and reactivity	Can form explosive mixture with air. May react violently with oxidants.
--------------------------	----------------------------------------------------------------------------

11 TOXICOLOGICAL INFORMATION

General	No known toxicological effects from this product.
---------	---------------------------------------------------

12 ECOLOGICAL INFORMATION

General	No known ecological damage caused by this product.
---------	----------------------------------------------------

13 DISPOSAL CONSIDERATIONS

General	Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required.
---------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

14 TRANSPORT INFORMATION

Proper shipping name	PROPANE
UN Nr	1978
Class	2

Safety Data Sheet

Product :**Propane**

Page :4/5

MSDS Nr : 302-00-0045BOC(A)

Version : 1.03

Date : 09/09/2003

Replaces version dated : 02/08/1994

ADR/RID Classification code	2F
ADR/RID Hazard Nr	23
Labelling ADR	Label 2.1: flammable gas
Other transport information	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured and: - cylinder valve is closed and not leaking - valve outlet cap nut or plug (where provided) is correctly fitted - valve protection device (where provided) is correctly fitted - there is adequate ventilation. - compliance with applicable regulations.

15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548	601-003-00-5.
EC Classification	F+;R12
-Symbols	F+: Extremely flammable
Labelling of cylinders	
-Symbols	Label 2.1: flammable gas
-Risk phrases	R12 Extremely flammable.
-Safety phrases	S9 Keep container in well ventilated place. S16 Keep away from ignition sources - No smoking. S33 Take precautionary measures against static discharges.

16 OTHER INFORMATION

Ensure all national/local regulations are observed.
Ensure operators understand the flammability hazard.
Contact with liquid may cause cold burns/frost bite.
The hazard of asphyxiation is often overlooked and must be stressed during operator training.
Users of breathing apparatus must be trained.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

Safety Data Sheet

Product :

Propane

Page :5/5

MSDS Nr : 302-00-0045BOC(A)

Version : 1.03

Date : 09/09/2003

Replaces version dated : 02/08/1994

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document.

Number of pages :5